


DPBB185N

Terminal Type - DPBB185N, High Current connectors, nominal voltage: 1000 V, nominal current: 353 A, Rated cross-section - 185 mm², connection method: Bolt connection, number of connections: 2, cross-section: 50 mm² - 185 mm², mounting type: TS 35/15, TS 32



Approvals



General Information

Product Name	DPBB185N
Connection Method	Bolt Connection
Rating	1000 V/353 A/185 mm ² /14 Nm
HSN Number	8904476703828
Standard Packing Qty(in No)	4
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	53 mm	2.09 inch
Length	115 mm	4.53 inch
Height	53.3 mm	2.1 inch
Weight of std. Packing Unit	1.49 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	50 mm ²
Conductor cross section flexible max	185 mm ²
Conductor cross section solid min	50 mm ²
Conductor cross section solid max	185 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	353 A
Nominal cross section	185 mm ²
Short-time current	22.2 kA
Rated surge voltage	12 kV
Degree of pollution	3

