



## DSET6

Terminal Type - DSET6 , Ground modular terminal block, connection method: Spring Cage Connection, number of connections: 2, Rated cross-section- 6.0 mm<sup>2</sup>, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 20 - 10, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	DSET6
Connection Method	Spring Cage Connection
Rating	NAP V/NAP A/6 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NAP

### Dimensions & Weight

Width	8 mm	0.31 inch
Length	74.5 mm	2.93 inch
Height	39.5 mm	1.56 inch
Weight of std. Packing Unit	2.07 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	6 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage $U_n$	NAP V
Nominal Current $I_n$	NAP A
Nominal cross section	6 mm <sup>2</sup>
Short-time current	0.72 kA
Rated surge voltage	NAP kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage $U_n$	V
ATEX Nominal Current $I_n$	A
ATEX Cross Sec. Flexible Max.	mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	0 V
B - CSA Nominal Current $I_N$	0 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	10 AWG

### Ratings - UL

UL Standard	
B - UL Nominal Voltage $U_N$	0 V
B - UL Nominal Current $I_N$	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG