


DST10-1X2

Terminal Type - DST10-1X2, Multi-Conductor terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm², connection method: Spring clamp connection, number of connections: 3, cross-section: 1.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DST10-1X2
Connection Method	Spring Cage Connection
Rating	1000 V/57 A/10 mm ² /NAP Nm
HSN Number	8904476702395
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	10 mm	0.39 inch
Length	97.5 mm	3.84 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.75 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki , Grey ,

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	57 A
Nominal cross section	10 mm ²
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

