



DST2.5-2C1P

Terminal Type - DST2.5-2C1P, Pluggable terminal block, nominal voltage: 500 V, nominal current: 16 A, Rated cross-section - 2.5 mm², connection method: Spring Cage connection, number of connections: 3, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DST2.5-2C1P
Connection Method	Spring Cage Connection
Rating	500 V/16 A/2.5 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	5.08 mm	0.2 inch
Length	66 mm	2.6 inch
Height	33 mm	1.3 inch
Weight of std. Packing Unit	0.86 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	16 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	4 kV
Degree of pollution	3

