



DST2.5-2X2

Terminal Type - DST2.5-2X2 , Multi-Conductor terminal block, nominal voltage:800 V, nominal current: 24 A, Rated cross-section - 2.5 mm², connection method: Spring clamp connection, number of connections: 4, cross section: 0.2 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

| | |
|-----------------------------|-------------------------------------|
| Product Name | DST2.5-2X2 |
| Connection Method | Spring Cage Connection |
| Rating | 800 V/24 A/2.5 mm ² / Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | NAP |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 5 mm | 0.2 inch |
| Length | 80 mm | 3.15 inch |
| Height | 33 mm | 1.3 inch |
| Weight of std. Packing Unit | 1.06 Kg | |

Material Data

| | |
|---------------------|---------------------------------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.2 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.2 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Ratings - IEC

| | |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 800 V |
| Nominal Current I_n | 24 A |
| Nominal cross section | 2.5 mm ² |
| Short-time current | 0.3 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

