


DST2.5

Terminal Type - DST2.5 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 24 A, connection method: Spring cage connection, number of connections: 2, Rated cross section: 2.5 mm², cross section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DST2.5
Connection Method	Spring Cage Connection
Rating	800 V/24 A/2.5 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	5 mm	0.2 inch
Length	53 mm	2.09 inch
Height	33 mm	1.3 inch
Weight of std. Packing Unit	0.64 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

