



DST4-2X2

Terminal Type - DST4-2X2 ,Multi-Conductor terminal block, nominal voltage: 800 V, nominal current: 32 A, Rated cross-section - 4.0 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DST4-2X2
Connection Method	Spring Cage Connection
Rating	800 V/32 A/4 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	86 mm	3.39 inch
Height	33.5 mm	1.32 inch
Weight of std. Packing Unit	1.49 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	32 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

