



DTB35-10X4

Terminal Type - DTB35-10, Hybrid Distribution Blocks, nominal voltage: 800 V, nominal current: 125 A, Rated cross-section -IC -35 mm², OG - 10 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: IC - 6-35 mm² - OG - 1.5-10 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DTB35-10X4
Connection Method	Spring Cage Connection
Rating	1000 V/125 A/IC -35 mm ² , OG - 10 mm ² mm ² /IC - 3 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	16.2 mm	0.64 inch
Length	86 mm	3.39 inch
Height	45 mm	1.77 inch
Weight of std. Packing Unit	2.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	IC- 6 mm ² , OG - 1.5 mm ² mm ²
Conductor cross section flexible max	IC- 35 mm ² , OG - 10 mm ² mm ²
Conductor cross section solid min	IC- 6 mm ² , OG - 1.5 mm ² mm ²
Conductor cross section solid max	IC- 35 mm ² , OG - 10 mm ² mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	125 A
Nominal cross section	IC -35 mm ² , OG - 10 mm ² mm ²
Short-time current	4.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

