



DTB35-10X4

Terminal Type - DTB35-10, Hybrid Distribution Blocks, nominal voltage: 800 V, nominal current: 125 A, Rated cross-section -IC -35 mm², OG - 10 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: IC - 6-35 mm² - OG - 1.5-10 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

| | |
|-----------------------------|--|
| Product Name | DTB35-10X4 |
| Connection Method | Spring Cage Connection |
| Rating | 1000 V/125 A/IC -35 mm ² , OG - 10 mm ² mm ² /IC - 3 Nm |
| HSN Number | 8904476704467 |
| Standard Packing Qty(in No) | 50 |
| Country Of Origin | India |
| Screw thread | NAV |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 16.2 mm | 0.64 inch |
| Length | 86 mm | 3.39 inch |
| Height | 45 mm | 1.77 inch |
| Weight of std. Packing Unit | 2.45 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , |

Rated Conductor Size

| | |
|--------------------------------------|--|
| Conductor cross section flexible min | IC- 6 mm ² , OG - 1.5 mm ² mm ² |
| Conductor cross section flexible max | IC- 35 mm ² , OG - 10 mm ² mm ² |
| Conductor cross section solid min | IC- 6 mm ² , OG - 1.5 mm ² mm ² |
| Conductor cross section solid max | IC- 35 mm ² , OG - 10 mm ² mm ² |

Ratings - IEC

| | |
|----------------------------------|--|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 1000 V |
| Nominal Current I_n | 125 A |
| Nominal cross section | IC -35 mm ² , OG - 10 mm ² mm ² |
| Short-time current | 4.2 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

