

DUTKD2.5TSWS

Terminal Type – DUTKD2.5TSWS , Knife Disconnect Terminal Block with test socket screw , nominal voltage: 1000 V, nominal current: 24 A, connection method: Screw connection, number of connections: 2, Rated cross section: 2.5 mm² , cross section: 0.5 mm² – 4 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32





Approvals

CE

General Information

Product Name	DUTKD2.5TSWS
Connection Method	Screw Connection with spring support
Rating	1000 V/24 A/2.5 mm^2/0.4 Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	5 mm	0.2 inch
Length	62 mm	2.44 inch
Height	53.5 mm	2.11 inch
Weight of std. Packing Unit	1.31 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm^2
Conductor cross section flexible max	2.5 mm^2
Conductor cross section solid min	0.5 mm^2
Conductor cross section solid max	4 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm^2
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3