



ETN2.5

Terminal Type - ETN2.5, Ground modular terminal block for photo voltaic applications, connection method: Screw connection, Rated cross-section- 2.5 mm², number of connections: 2, cross-section: 0.5 mm² - 4 mm², AWG: 24-14, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	ETN2.5
Connection Method	Screw Connection
Rating	NAP V/NAP A/2.5 mm ² /0.5 Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

Dimensions & Weight

Width	5 mm	0.2 inch
Length	45.6 mm	1.8 inch
Height	51.55 mm	2.03 inch
Weight of std. Packing Unit	1.77 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	NAP kV
Degree of pollution	3

