


KNL4

Neutral link Type - KNL4 , Neutral link for shield on busbars, Nominal voltage: 800 V , Nominal current: 41 A, Connection method: Screw connection, number of connections: 1, Rated cross section: 6.0 mm² , cross section: 0.5 mm² - 6 mm², mounting type: Neutral Busbar



Approvals

CE

General Information

Product Name	KNL4
Connection Method	Screw Connection
Rating	800 V/41 A/6 mm ² /0.8 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	24 mm	0.94 inch
Height	30 mm	1.18 inch
Weight of std. Packing Unit	0.66 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green
Colour Variants	Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	NAP kA
Rated surge voltage	NAP kV
Degree of pollution	3

