


KBTM4C

Terminal Type - KBTM4C , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm², connection method: Bolt connection - Nut Driver Operated, number of connections: 2, Rated Cross section: 10 mm² , cross-section: 0.5 mm² - 10 mm², AWG: 14 - 8, mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KBTM4C
Connection Method	Bolt Connection
Rating	1000 V/57 A/10 mm ² /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	14.5 mm	0.57 inch
Length	50 mm	1.97 inch
Height	41.5 mm	1.63 inch
Weight of std. Packing Unit	1.16 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	57 A
Nominal cross section	10 mm ²
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	30 A
B - CSA Wire Min	14 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	30 A
B - UL Wire Min	14 AWG
B - UL Wire Max	8 AWG