


## **KBTM4C**

Terminal Type - KBTM4C , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm<sup>2</sup>, connection method: Bolt connection - Nut Driver Operated, number of connections: 2, Rated Cross section: 10 mm<sup>2</sup> , cross-section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 14 - 8, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals



### General Information

Product Name	KBTM4C
Connection Method	Bolt Connection
Rating	1000 V/57 A/10 mm <sup>2</sup> /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	14.5 mm	0.57 inch
Length	50 mm	1.97 inch
Height	41.5 mm	1.63 inch
Weight of std. Packing Unit	1.16 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	57 A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage $U_n$	V
ATEX Nominal Current $I_n$	A
ATEX Cross Sec. Flexible Max.	mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	600 V
B - CSA Nominal Current $I_N$	30 A
B - CSA Wire Min	14 AWG
B - CSA Wire Max	8 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	30 A
B - UL Wire Min	14 AWG
B - UL Wire Max	8 AWG