


KBTM5-15C

Terminal Type - KBTM5-15C, Feed Through Terminal Block with hinged covers, nominal voltage: 800 V (Tested at 1100 V), nominal current: 76 A, Rated Cross Section: 16 mm² connection method: Bolt Connection - Nut driver Operated, number of connections: 2, cross section: 0.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KBTM5-15C
Connection Method	Bolt Connection
Rating	800 V/76 A/16 mm ² /2 Nm
HSN Number	8904476704733
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M5

Dimensions & Weight

Width	16.5 mm	0.65 inch
Length	50 mm	1.97 inch
Height	41.4 mm	1.63 inch
Weight of std. Packing Unit	1.3 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	76 A
Nominal cross section	16 mm ²
Short-time current	1.92 kA
Rated surge voltage	8 kV
Degree of pollution	3

