


KBTM6C

Terminal Type - KBTM6C, Feed Through Terminal Block with hinged cover, nominal voltage: 800 V, nominal current: 101 A, connection method: Bolt Connection - Nut driver operated, number of connections: 2, Rated cross section: 25 mm², cross section: 6 mm² - 25 mm², AWG: 14 - 4, mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KBTM6C
Connection Method	Bolt Connection
Rating	800 V/101 A/25 mm ² /2.5 Nm
HSN Number	8904476704566
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M6

Dimensions & Weight

Width	18.5 mm	0.73 inch
Length	50 mm	1.97 inch
Height	41.4 mm	1.63 inch
Weight of std. Packing Unit	1.9 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	25 mm ²
Conductor cross section solid min	6 mm ²
Conductor cross section solid max	25 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	101 A
Nominal cross section	25 mm ²
Short-time current	3 kA
Rated surge voltage	8 kV
Degree of pollution	3

