
KNL16

Neutral link Type - KNL16 , Neutral link for shield on busbars, Nominal voltage: 800 V , Nominal current: 76 A, Connection method: Screw connection, number of connections: 1, Rated cross section: 16.0 mm² , cross section: 6.0 mm² - 16.0 mm², mounting type: Neutral Busbar



Approvals

CE

General Information

Product Name	KNL16
Connection Method	Screw Connection
Rating	800 V/76 A/16 mm^2/2.0 Nm
HSN Number	8904476705402
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	9.7 mm	0.38 inch
Length	24 mm	0.94 inch
Height	36.3 mm	1.43 inch
Weight of std. Packing Unit	0.8 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green
Colour Variants	Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	6 mm^2
Conductor cross section flexible max	16 mm^2
Conductor cross section solid min	6 mm^2
Conductor cross section solid max	16 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	76 A
Nominal cross section	16 mm^2
Short-time current	NAP kA
Rated surge voltage	NAV kV
Degree of pollution	3