KNL35

Neutral link Type - KNL35 , Neutral link for shield on busbars, Nominal voltage: 800 V , Nominal current: 125 A, Connection method: Screw connection, number of connections: 1, Rated cross section: 35.0 mm² , cross section: 10.0 mm² - 35.0 mm², mounting type: Neutral Busbar



Approvals

CE

General Information

Product Name	KNL35
Connection Method	Screw Connection
Rating	800 V/125 A/35 mm^2/3.0 Nm
HSN Number	8904476705419
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	14.3 mm	0.56 inch
Length	27.3 mm	1.07 inch
Height	45 mm	1.77 inch
Weight of std. Packing Unit	1.13 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green
Colour Variants	Black , Green ,

Rated Conductor Size

Conductor cross section flexible min	10 mm^2
Conductor cross section flexible max	35 mm^2
Conductor cross section solid min	10 mm^2
Conductor cross section solid max	35 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	125 A
Nominal cross section	35 mm^2
Short-time current	NAP kA
Rated surge voltage	NAP kV
Degree of pollution	3