



KU2D4S

Terminal Type - KU2D4S , Multi level terminal block with equipotential bonder, nominal voltage: 500 V, nominal current: 24 A, connection method: Screw connection, number of connections: 4, Rated cross section - 2.5 mm², cross-section: 0.5 mm² - 4 mm², AWG: 20 - 12, mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KU2D4S
Connection Method	Screw Connection
Rating	500 V/24 A/2.5 mm ² /0.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	50 mm	1.97 inch
Height	50.8 mm	2 inch
Weight of std. Packing Unit	1.47 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	6 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	250 V
ATEX Nominal Current I_n	21 A
ATEX Cross Sec. Flexible Max.	2.5 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	20 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	20 A
B - UL Wire Min	20 AWG
B - UL Wire Max	12 AWG