



KUDD4

Terminal Type - KUDD4 , Multi level terminal block, nominal voltage: 500 V, nominal current: 24 A, Rated cross-section: 2.5 mm² , connection method: Screw connection, number of connections: 4, cross section: 0.5 mm² - 4 mm², AWG: 20 - 12 , mounting type: TS35/7.5 , TS35/15 ,and TS32



Approvals



General Information

| | |
|-----------------------------|--|
| Product Name | KUDD4 |
| Connection Method | Screw Connection |
| Rating | 500 V/24 A/2.5 mm ² /0.4 Nm |
| HSN Number | 8904476704405 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | M3 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 6 mm | 0.24 inch |
| Length | 54 mm | 2.13 inch |
| Height | 59.7 mm | 2.35 inch |
| Weight of std. Packing Unit | 1.44 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 4 mm ² |

Ratings - IEC

| | |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 500 V |
| Nominal Current I_n | 24 A |
| Nominal cross section | 2.5 mm ² |
| Short-time current | 0.3 kA |
| Rated surge voltage | 6 kV |
| Degree of pollution | 3 |

Ratings - ATEX

| | |
|-------------------------------|---------------------|
| ATEX Standard | EN 60079-7 |
| ATEX Nominal Voltage U_n | 250 V |
| ATEX Nominal Current I_n | 21 A |
| ATEX Cross Sec. Flexible Max. | 2.5 mm ² |

Ratings - CSA

| | |
|-------------------------------|------------------|
| CSA Standard | CSA C22.2 NO 158 |
| B - CSA Nominal Voltage U_N | 600 V |
| B - CSA Nominal Current I_N | 20 A |
| B - CSA Wire Min | 20 AWG |
| B - CSA Wire Max | 12 AWG |

Ratings - UL

| | |
|------------------------------|---------|
| UL Standard | UL 1059 |
| B - UL Nominal Voltage U_N | 600 V |
| B - UL Nominal Current I_N | 20 A |
| B - UL Wire Min | 20 AWG |
| B - UL Wire Max | 12 AWG |