



## KUDD4D4

Terminal Type - KUDD4D4, Multi level terminal block with build in diode, nominal voltage: 500 V, nominal current: 1 A, with integrated diode, Rated cross-section: 2.5 mm<sup>2</sup>, connection method: Screw connection, number of connections: 4, cross section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS35/7.5, TS35/15, and TS32



### Approvals



### General Information

Product Name	KUDD4D4
Connection Method	Screw Connection
Rating	500 V/Diode Current - 1 A/2.5 mm <sup>2</sup> /0.4 Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	54 mm	2.13 inch
Height	59.7 mm	2.35 inch
Weight of std. Packing Unit	1.39 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	500 V
Nominal Current $I_n$	Diode Current - 1 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	6 kV
Degree of pollution	3

