KUDF4

Terminal Type - KUDF4, Fuse terminal block, nominal voltage: 800 V, nominal current: 6.3 A, suitable size of cartridge fuse : 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, Rated cross section - 4 mm², cross section: 0.5 mm² - 4 mm², AWG: 20-12, mounting type: TS 35/7.5, TS 35/15 , TS 32





Approvals

General Information

Product Name	KUDF4
Connection Method	Screw Connection
Rating	800 V/6.3 A/4 mm^2/0.4 Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	8 mm	0.31 inch
Length	54.5 mm	2.15 inch
Height	47.8 mm	1.88 inch
Weight of std. Packing Unit	1.5 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm^2
Conductor cross section flexible max	4 mm^2
Conductor cross section solid min	0.5 mm^2
Conductor cross section solid max	4 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-3
Nominal Voltage U_n	800 V
Nominal Current I_n	6.3 A
Nominal cross section	4 mm^2
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	420 V
ATEX Nominal Current I_n	5 A
ATEX Cross Sec. Flexible Max.	2.5 mm^2

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	6.3 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	7 A
B - UL Wire Min	20 AWG
B - UL Wire Max	12 AWG