



## KUF10

Terminal Type - KUF10, Fuse terminal block, nominal voltage: 1000 V, nominal current: 12 A, Rated cross-section - 10 mm<sup>2</sup>, suitable size of cartridge fuse: 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 18 - 6, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals



### General Information

Product Name	KUF10
Connection Method	Screw Connection
Rating	1000 V/12 A/10 mm <sup>2</sup> /1.4 Nm
HSN Number	8904476704436
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	12 mm	0.47 inch
Length	66 mm	2.6 inch
Height	65.6 mm	2.58 inch
Weight of std. Packing Unit	2.07 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 6947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	12 A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage $U_n$	750 V
ATEX Nominal Current $I_n$	10 A
ATEX Cross Sec. Flexible Max.	10 mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	600 V
B - CSA Nominal Current $I_N$	12 A
B - CSA Wire Min	18 AWG
B - CSA Wire Max	6 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	12 A
B - UL Wire Min	18 AWG
B - UL Wire Max	6 AWG