


KULTD4

Terminal Type - KULTD4 , Knife Disconnect Terminal Block, nominal voltage: 800 V, nominal current: 20 A, Rated cross section: 4.0mm² , connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 4 mm², AWG: 24 - 10 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KULTD4
Connection Method	Screw Connection
Rating	800 V/20 A/4 mm ² /0.6 Nm
HSN Number	8904476703491
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	53 mm	2.09 inch
Height	55.9 mm	2.2 inch
Weight of std. Packing Unit	1.31 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	20 A
Nominal cross section	4 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	C22.2 No.158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	15 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	15 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG