


KUT25

Terminal Type - KUT25 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 101 A, connection method: Screw connection, number of connections: 2, Rated cross section: 25 mm², cross section: 6 mm² - 25 mm², AWG: 2-10, mounting type: TS 35/7.5 , TS 35/15 , and TS 32



Approvals



General Information

Product Name	KUT25
Connection Method	Screw Connection
Rating	1000 V/101 A/25 mm ² /2.3 Nm
HSN Number	8904476702135
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	12 mm	0.47 inch
Length	45 mm	1.77 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	1.84 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	25 mm ²
Conductor cross section solid min	6 mm ²
Conductor cross section solid max	25 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	101 A
Nominal cross section	25 mm ²
Short-time current	3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN-60079-7
ATEX Nominal Voltage U_n	630 V
ATEX Nominal Current I_n	101 A
ATEX Cross Sec. Flexible Max.	16 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	115 A
B - CSA Wire Min	10 AWG
B - CSA Wire Max	2 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	115 A
B - UL Wire Min	10 AWG
B - UL Wire Max	2 AWG