


KUT4

Terminal Type - KUT4 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 32 A, Tested at - 1100 V, connection method: Screw connection, number of connections: 2, Rated cross section: 4.0 mm² , cross section: 0.5 mm² - 6 mm², AWG: 20 - 10, mounting type: TS35/7.5 , TS35/15 , TS32 and TS15



Approvals



General Information

Product Name	KUT4
Connection Method	Screw Connection
Rating	800 V/32 A/4 mm ² /0.5 Nm
HSN Number	8904476702074
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6.7 mm	0.26 inch
Length	42.5 mm	1.67 inch
Height	46.4 mm	1.83 inch
Weight of std. Packing Unit	1.19 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	32 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	500 V
ATEX Nominal Current I_n	32 A
ATEX Cross Sec. Flexible Max.	4 mm ²

Ratings - CSA

CSA Standard	CSA 22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	35 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	10 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	35 A
B - UL Wire Min	20 AWG
B - UL Wire Max	10 AWG