


KUT95

Terminal Type - KUT95 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 232 A, connection method: Screw clamp connection , Operated by - 6 mm Allen key , number of connections: 2, Rated cross section: 95 mm², cross section: 25 mm² - 120 mm², AWG: 4/0 - 2 , mounting type: TS35/7.5 , TS35/15 , and TS32



Approvals



General Information

Product Name	KUT95
Connection Method	Screw Connection
Rating	1000 V/232 A/95 mm ² /6 Nm
HSN Number	8904476702173
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M8

Dimensions & Weight

Width	25 mm	0.98 inch
Length	83 mm	3.27 inch
Height	90 mm	3.54 inch
Weight of std. Packing Unit	2.29 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	95 mm ²
Conductor cross section solid min	25 mm ²
Conductor cross section solid max	120 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	232 A
Nominal cross section	95 mm ²
Short-time current	11.40 kA
Rated surge voltage	12 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN-60079-7
ATEX Nominal Voltage U_n	1000 V
ATEX Nominal Current I_n	232 A
ATEX Cross Sec. Flexible Max.	95 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	230 A
B - CSA Wire Min	2 AWG
B - CSA Wire Max	4/0 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	230 A
B - UL Wire Min	2 AWG
B - UL Wire Max	4/0 AWG