



## KUTD10

Terminal type - KUTD10, Test disconnect terminal block, nom. voltage: 630 V, nominal current: 61 A, Rated cross-section- 10 mm<sup>2</sup> , Connection Possibility: 1.5 mm<sup>2</sup> - 16 mm<sup>2</sup> , AWG : 10-6 , connection method: screw connection, Mounting type - TS 35/15, TS 35/7.5



### Approvals



### General Information

Product Name	KUTD10
Connection Method	Screw Connection
Rating	630 V/61 A/10 mm <sup>2</sup> /1.2 Nm
HSN Number	8904476702289
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M4

### Dimensions & Weight

Width	8 mm	0.31 inch
Length	61.7 mm	2.43 inch
Height	57.6 mm	2.27 inch
Weight of std. Packing Unit	1.69 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	16 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	630 V
Nominal Current $I_n$	61 A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage $U_n$	630 V
ATEX Nominal Current $I_n$	61 A
ATEX Cross Sec. Flexible Max.	10 mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	600 V
B - CSA Nominal Current $I_N$	65 A
B - CSA Wire Min	10 AWG
B - CSA Wire Max	6 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	65 A
B - UL Wire Min	10 AWG
B - UL Wire Max	6 AWG