


KUTSD6-2WAY

Terminal Type - KUTSD6-2WAY , Disconnecting terminal block, nominal voltage: 800 V, nominal current: 41 A, connection method: Screw connection, Rated cross-section- 6 mm², number of connections: 4, cross section: 0.5 mm² - 10 mm², AWG: 20-8 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KUTSD6-2WAY
Connection Method	Screw Connection
Rating	800 V/41 A/6 mm ² /1.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	INDIA
Screw thread	M3.5

Dimensions & Weight

Width	16 mm	0.63 inch
Length	65 mm	2.56 inch
Height	46.7 mm	1.84 inch
Weight of std. Packing Unit	1.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

