

# *LPT225*

Terminal Type - LPT225, Feed-through terminal block, nominal voltage: 400 V, nominal current: 101 A, connection method: Screw connection, Operated by - 3mm / 4 mm Allen key, number of connections: 3, cross section: 4 mm² - 25 mm², mounting type: TS 35/7.5, TS 35/15, TS 32





## Approvals

CE

## General Information

| | |
|---|---|
| Product Name | LPT225 |
| Connection Method | Screw Connection |
| Rating | 400 V/101 A/IC - 25 mm², OG - 4 mm²/3 Nm |
| HSN Number | 8904476703545 |
| Standard Packing Qty(in No) | 10 |
| Country Of Origin | India |
| Screw thread | NA |

## Dimensions & Weight

| | | |
|---|---|---|
| Width | 10.8 mm | 0.43 inch |
| Length | 42 mm | 1.65 inch |
| Height | 43.6 mm | 1.72 inch |
| Weight of std. Packing Unit | 0.48 Kg | |

## Material Data

| | |
|---|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | |

## Rated Conductor Size

| | |
|---|---|
| Conductor cross section flexible min | 4 mm² |
| Conductor cross section flexible max | 25 mm² |
| Conductor cross section solid min | 4 mm² |
| Conductor cross section solid max | 25 mm² |

## Ratings - IEC

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage $U_n$ | 400 V |
| Nominal Current $I_n$ | 101 A |
| Nominal cross section | IC - 25 mm², OG - 4 $mm^2$ |
| Short-time current | 3 kA |
| Rated surge voltage | 4 kV |
| Degree of pollution | 3 |