



LPT325NV

Terminal Type - LPT325NV , Feed-through terminal block, nominal voltage: 630 V, nominal current: 101 A, connection method: Screw connection, Operated by - 3 mm Allen key , number of connections: 4 , cross section: IC - 16 - 25 mm², OG - 6 - 10 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	LPT325NV
Connection Method	Screw Connection
Rating	630 V/101 A/IC - 25 mm ² , OG - 10 mm ² /2.5 Nm
HSN Number	NAV
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	11.7 mm	0.46 inch
Length	56.3 mm	2.22 inch
Height	58 mm	2.28 inch
Weight of std. Packing Unit	0.48 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	IC-16 mm ² , OG-6 mm ²
Conductor cross section flexible max	IC-25 mm ² , OG-10 mm ²
Conductor cross section solid min	IC-16 mm ² , OG-6 mm ²
Conductor cross section solid max	IC-25 mm ² , OG-10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	630 V
Nominal Current I_n	101 A
Nominal cross section	IC - 25 mm ² , OG - 10 mm ²
Short-time current	3 kA
Rated surge voltage	4 kV
Degree of pollution	3

