

# LPT335

Terminal Type - LPT335, Feed-through terminal block, nominal voltage: 400 V, nominal current: 125 A, connection method: Screw connection, Operated by - 3 mm / 4 mm Allen key, number of connections: 4, Rated Cross section: 35 mm², cross section: 6 mm² - 35 mm², mounting type: TS 35/7.5, TS 35/15, TS 32





## Approvals

CE

## General Information

| | |
|---|---|
| Product Name | LPT335 |
| Connection Method | Screw Connection |
| Rating | 400 V/125 A/IC - 35 mm², OG - 6 mm²/IC-6 Nm, OG-3 Nm |
| HSN Number | NAV |
| Standard Packing Qty(in No) | 10 |
| Country Of Origin | India |
| Screw thread | NAP |

## Dimensions & Weight

| | | |
|---|---|---|
| Width | 14.3 mm | 0.56 inch |
| Length | 53.5 mm | 2.11 inch |
| Height | 65.5 mm | 2.58 inch |
| Weight of std. Packing Unit | 1.68 Kg | |

## Material Data

| | |
|---|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khaki , |

## Rated Conductor Size

| | |
|---|---|
| Conductor cross section flexible min | 6 mm² |
| Conductor cross section flexible max | 35 mm² |
| Conductor cross section solid min | 6 mm² |
| Conductor cross section solid max | 35 mm² |

## Ratings - IEC

| | |
|---|---|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage $U_n$ | 400 V |
| Nominal Current $I_n$ | 125 A |
| Nominal cross section | IC - 35 mm², OG - 6 $mm^2$ |
| Short-time current | 4.2 kA |
| Rated surge voltage | 4 kV |
| Degree of pollution | 3 |