


## ONTM4-10C

Terminal Type - ONTM4-10C , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 57 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2, Rated Cross-section : 10 mm<sup>2</sup> , cross section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15 , TS 32



### Approvals



### General Information

|                             |                                        |
|-----------------------------|----------------------------------------|
| Product Name                | ONTM4-10C                              |
| Connection Method           | Bolt Connection                        |
| Rating                      | 1000 V/57 A/10 mm <sup>2</sup> /1.2 Nm |
| HSN Number                  | 85389000                               |
| Standard Packing Qty(in No) | 50                                     |
| Country Of Origin           | India                                  |
| Screw thread                | M4                                     |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 13 mm   | 0.51 inch |
| Length                      | 48 mm   | 1.89 inch |
| Height                      | 36.5 mm | 1.44 inch |
| Weight of std. Packing Unit | 1.08 Kg |           |

### Material Data

|                     |                                                |
|---------------------|------------------------------------------------|
| Insulating Material | Polyamide 6,6                                  |
| Standard Colour     | Gray                                           |
| Colour Variants     | Red , Yellow , Blue , Black , Green , Khakhi , |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 1.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 10 mm <sup>2</sup>  |
| Conductor cross section solid min    | 1.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 10 mm <sup>2</sup>  |

## Ratings - IEC

|                                  |                    |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC 60947-7-1      |
| Nominal Voltage $U_n$            | 1000 V             |
| Nominal Current $I_n$            | 57 A               |
| Nominal cross section            | 10 mm <sup>2</sup> |
| Short-time current               | 1.2 kA             |
| Rated surge voltage              | 8 kV               |
| Degree of pollution              | 3                  |

