



## PGQ1.5

Terminal Type - PGQ 1.5, Ground modular terminal block , connection method: push in connection , number of connections: 2, cross section: 0.08 mm<sup>2</sup> - 2.5 mm<sup>2</sup> , mounting type: TS 35/7.5, TS 35/15.



### Approvals



### General Information

Product Name	PGQ1.5
Connection Method	Push In Connection
Rating	NAP V/NAP A/1.5 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NAP

### Dimensions & Weight

Width	3.5 mm	0.14 inch
Length	47.56 mm	1.87 inch
Height	30.7 mm	1.21 inch
Weight of std. Packing Unit	0.4 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	1.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage $U_n$	NAP V
Nominal Current $I_n$	NAP A
Nominal cross section	1.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	0 kV
Degree of pollution	3

