


PQ1.5-1X2

Terminal Type - PQ1.5-1X2, Multi conductor Feed-through terminal block, nominal voltage: 1000 V, nominal current: 17.5 A, Rated cross-section - 1.5 mm², connection method: Push-in connection, number of connections: 3, cross-section: 0.2 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	PQ1.5-1X2
Connection Method	Push In Connection
Rating	1000 V/17.5 A/1.5 mm ² /NAP Nm
HSN Number	8904476705884
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	3.5 mm	0.14 inch
Length	56.5 mm	2.22 inch
Height	30.5 mm	1.2 inch
Weight of std. Packing Unit	0.53 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	1.5 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	17.5 A
Nominal cross section	1.5 mm ²
Short-time current	0.18 kA
Rated surge voltage	8 kV
Degree of pollution	3

