



## PQ2.5-2T2P

Terminal Type - PQ2.5-2T2P , Multi tier Feed Through terminal block, connection method: Push-in connection/ plug connection, nominal voltage: 500 V , nominal current: 22 A , Rated cross-section - 2.5 mm<sup>2</sup> , number of connections: 4, cross-section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG : 24-12 , mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	PQ2.5-2T2P
Connection Method	Push In Connection
Rating	500 V/22 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	73.2 mm	2.88 inch
Height	50 mm	1.97 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	500 V
Nominal Current $I_n$	22 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	6 kV
Degree of pollution	3

