


PQ2.5-2X2+D2

Terminal Type - PQ 2.5-2X2+D2, Multi Conductor terminal block with build in diode, nominal voltage: 1000 V, nominal current: 1 A, Rated cross section: 2.5 mm², connection method: Push-in connection, number of connections: 4, cross section: 0.08 mm² - 4 mm², AWG : 24-12, color: Gray, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	PQ2.5-2X2+D2
Connection Method	Push In Connection
Rating	1000 V/Diode Current - 1 A/2.5 mm ² /NAP Nm
HSN Number	8904476705280
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	5 mm	0.2 inch
Length	74.4 mm	2.93 inch
Height	36 mm	1.42 inch
Weight of std. Packing Unit	1.02 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.14 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	Diode Current - 1 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

