



PQ4-2T

Terminal Type - PQ4-2T, Multi level terminal block, nominal voltage: 1000 V, nominal current: 28 A, connection method: Push in type, number of connections: 4, cross section: 0.08 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PQ4-2T
Connection Method	Push In Connection
Rating	1000 V/28 A/4 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	99.3 mm	3.91 inch
Height	49.6 mm	1.95 inch
Weight of std. Packing Unit	1.07 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	28 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

