



PQD6

Terminal Type - PQD6 , Knife Disconnect Terminal Blocks , nominal voltage: 1000 V, nominal current: 30 A, Rated Cross section - 6 mm², connection method: Push in type, number of connections: 2, cross-section: 0.2 mm² - 10 mm², AWG : 24-8 , mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PQD6
Connection Method	Push In Connection
Rating	1000 V/30 A/6 mm ² /NAV Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	8 mm	0.31 inch
Length	104.2 mm	4.1 inch
Height	47.6 mm	1.87 inch
Weight of std. Packing Unit	1.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	30 A
Nominal cross section	6 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	500 V
ATEX Nominal Current I_n	30 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	35 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	35 A
B - UL Wire Min	24 AWG
B - UL Wire Max	8 AWG