

PQF4AD240V

Terminal Type - PQF4AD240V, Fuse Terminal block, nominal voltage: 240V, nominal current: 6.3 A, Rated cross-section - 4 mm²- suitable size of cartridge fuse : 5X20 mm, connection method: Push in connection, number of connections: 2, cross section: 0.08 mm² - 6 mm², AWG: 24-10, mounting type: TS 35/7.5, TS 35/15.





Approvals

CE

General Information

Product Name	PQF4AD240V
Connection Method	Push In Connection
Rating	240 V/6.3 A/4 mm^2/NAP Nm
HSN Number	8904476700827
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	56.2 mm	2.21 inch
Height	61.1 mm	2.41 inch
Weight of std. Packing Unit	1.72 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	4 mm^2
Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	6 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-3
Nominal Voltage U_n	240 V
Nominal Current I_n	6.3 A
Nominal cross section	4 mm^2
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3