



PQK4-2T

Terminal Type - PQK4-2T , Multi-tier terminal block with Knife Disconnect feature in the upper tier, nominal voltage: 1000 V, nominal current: UT:22 A, LT:28 A, Rated cross section: 4.0 mm² , connection method: Push in connection, number of connections: 4, cross section: 0.08 mm² - 6 mm²



Approvals



General Information

Product Name	PQK4-2T
Connection Method	Push In Connection
Rating	1000 V/UT-22 A, LT-28 A/4 mm ² / Nm
HSN Number	85389000
Standard Packing Qty(in No)	0
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	99.3 mm	3.91 inch
Height	50.5 mm	1.99 inch
Weight of std. Packing Unit	0 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	UT-22 A, LT-28 A
Nominal cross section	4 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

