


PQPP2.5F-2W

Plug Type - PQPP2.5F-2W , nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection, number of connections: 2, cross section: 0.08 mm² - 4 mm², AWG : 24-12



Approvals



General Information

Product Name	PQPP2.5F-2W
Connection Method	Push In Connection
Rating	500 V/24 A/2.5 mm ² /NAP Nm
HSN Number	NAV
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	10 mm	0.39 inch
Length	15.8 mm	0.62 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	0.73 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

