

PQPP2.5M-VM8W

Socket Type - PQPP2.5M-VM8W , nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection, number of connections: 8, number of positions: 8, cross section: 0.08 mm² - 4 mm², AWG : 24-12, mounting type: Panel mounting / Surface mounting (Vertical type)



Approvals



General Information

| | |
|-----------------------------|--|
| Product Name | PQPP2.5M-VM8W |
| Connection Method | Push In Connection |
| Rating | 500 V/24 A/2.5 mm ² /NAP Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | NAP |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 55.5 mm | 2.19 inch |
| Length | 18.8 mm | 0.74 inch |
| Height | 38 mm | 1.5 inch |
| Weight of std. Packing Unit | 2.94 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , |

Rated Conductor Size

| | |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.14 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.08 mm ² |
| Conductor cross section solid max | 4 mm ² |

Ratings - IEC

| | |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 500 V |
| Nominal Current I_n | 24 A |
| Nominal cross section | 2.5 mm ² |
| Short-time current | 0.3 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

