

PQT2.5

Terminal Type - PQT2.5, PCB Connector, nominal voltage: 500 V, nominal current: 15 A, connection method: Pushing connection, number of connections: 1 , cross-section: 0.5 mm² - 2.5 mm², AWG: 24 - 12, mounting type - Printed circuit board (PCB)



Approvals



General Information

Product Name	PQT2.5
Connection Method	Push In Connection
Rating	500 V/15 A/2.5 mm ² /NAV Nm
HSN Number	85389000
Standard Packing Qty(in No)	250
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	7.5 mm	0.3 inch
Length	19 mm	0.75 inch
Height	23.7 mm	0.93 inch
Weight of std. Packing Unit	1.08 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	15 A
Nominal cross section	2.5 mm ²
Short-time current	NAV kA
Rated surge voltage	2 kV
Degree of pollution	3

