



SCET4

Terminal Type - SCET4 , Ground terminal block, connection method: Spring Cage connection with side wire entry, number of connections: 2, Rated cross section : 4 mm², cross section: 0.5 mm² - 4 mm², AWG: 20 - 12, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SCET4
Connection Method	Spring Cage Connection
Rating	NAP V/NAP A/4 mm ² /NAP Nm
HSN Number	8904476704078
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NA

Dimensions & Weight

Width	6 mm	0.24 inch
Length	44.5 mm	1.75 inch
Height	39.6 mm	1.56 inch
Weight of std. Packing Unit	1.03 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green_Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	AWG
B - CSA Wire Max	AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	V
B - UL Nominal Current I_N	A
B - UL Wire Min	20 AWG
B - UL Wire Max	12 AWG