


SPT240

Terminal Type – SPT240, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, Rated cross-section – 240 mm², nominal current: 415 A, connection method: Bolt connection, number of connections: 2, cross-section: 25 mm² – 240 mm², 8 AWG - 600 KCMIL, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SPT240
Connection Method	Bolt Connection
Rating	1000 V/415 A/240 mm ² /14 Nm
HSN Number	8904476702630
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	55 mm	2.17 inch
Length	286.8 mm	11.29 inch
Height	89.3 mm	3.52 inch
Weight of std. Packing Unit	2.7 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	240 mm ²
Conductor cross section solid min	25 mm ²
Conductor cross section solid max	240 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	415 A
Nominal cross section	240 mm ²
Short-time current	28.80 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	1000 V
ATEX Nominal Current I_n	415 A
ATEX Cross Sec. Flexible Max.	240 mm ²

Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	AWG
B - CSA Wire Max	KCMIL

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	1000 V
B - UL Nominal Current I_N	420 A
B - UL Wire Min	8 AWG
B - UL Wire Max	600 KCMIL