


SQ16-1X2

Terminal Type - SQ16-1X2 , Multi conductor feed through terminal block, nominal voltage: 1000 V, nominal current: 76 A, connection method: Spring Cage Connection, number of connections: 2, cross section: 0.2 mm² - 25 mm², AWG: 24-4 , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SQ16-1X2
Connection Method	Spring Cage Connection
Rating	1000 V/76 A/16 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	INDIA
Screw thread	NAP

Dimensions & Weight

Width	12 mm	0.47 inch
Length	110.3 mm	4.34 inch
Height	50.5 mm	1.99 inch
Weight of std. Packing Unit	1.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	25 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	76 A
Nominal cross section	16 mm ²
Short-time current	1.92 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	85 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	4 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	85 A
B - UL Wire Min	24 AWG
B - UL Wire Max	4 AWG