



SQ2.5-3T

Terminal Type - SQ2.5-3T , Multi-tier Feed Through terminal block, connection method: Spring cage connection, nominal voltage : 1000 V , nominal current : Upper Tier - 24 A , Middle Tier - 24 A , Lower Tier - 24 A, Rated cross-section: 2.5 mm², number of connections: 4, cross-section: 0.08 mm² - 4 mm²,AWG 24-12 mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SQ2.5-3T
Connection Method	Spring Cage Connection
Rating	1000 V/24 A/2.5 mm ² /NAP Nm
HSN Number	8904476701039
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	5 mm	0.2 inch
Length	107.7 mm	4.24 inch
Height	58 mm	2.28 inch
Weight of std. Packing Unit	0.62 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60049-7
ATEX Nominal Voltage U_n	630 V
ATEX Nominal Current I_n	18 A
ATEX Cross Sec. Flexible Max.	2.5 mm ²

Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	AWG
B - CSA Wire Max	AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	20 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG