SQF4AD110V

Terminal Type - SQF4AD110V, Fuse Terminal block, nominal voltage: 110 V, nominal current: 6.3 A, Rated cross section: 4.0 mm², suitable size of cartridge fuse : 5X20 mm, connection method: Spring Cage connection, number of connections: 2, cross section: 0.08 mm² - 6 mm², AWG: 24-10, mounting type: TS 35/7.5, TS 35/15





Approvals

General Information

Product Name	SQF4AD110V
Connection Method	Spring Cage Connection
Rating	110 V/6.3 A/4 mm^2/NAP Nm
HSN Number	8904476701220
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	62.4 mm	2.46 inch
Height	61.2 mm	2.41 inch
Weight of std. Packing Unit	1.74 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.08 mm^2
Conductor cross section flexible max	4 mm^2
Conductor cross section solid min	0.08 mm^2
Conductor cross section solid max	6 mm^2

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1 , IEC 60947-7-3
Nominal Voltage U_n	110 V
Nominal Current I_n	6.3 A
Nominal cross section	4 mm^2
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3