


## SQTP2.5P4-4W

Terminal Type -SQTP2.5P4-4W , Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A , connection method: Spring Cage Connection, number of connections: 16, Rated cross section: 2.5 mm<sup>2</sup> , cross-section: 0.08 mm<sup>2</sup> – 4 mm<sup>2</sup>, AWG: 24-12 , mounting type: Panel Mounted



### Approvals



### General Information

Product Name	SQTP2.5P4-4W
Connection Method	Spring Cage Connection
Rating	800 V/24 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	8904476701428
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	55.8 mm	2.2 inch
Length	32 mm	1.26 inch
Height	22 mm	0.87 inch
Weight of std. Packing Unit	0.4 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC60947-7-1
Nominal Voltage $U_n$	800 V
Nominal Current $I_n$	24 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

